

**SPECIFICATIONS OF COLOR LCD FISH FINDER
FCV-288**

1 GENERAL

- 1.1 TX frequency 50 kHz and 200 kHz, dual frequency transmission
- 1.2 Output power 1, 2 or 3 kW selectable
- 1.3 Power reduction Auto, 10 to 100% (10% step)
- 1.4 TX rate Max. 3000 pulse/min
- 1.5 Pulse length Max. 3 msec

2 DISPLAY UNIT

- 2.1 Display mode 10.4-inch color LCD, 640 x 480 dots
- 2.2 Brilliance 300 cd
- 2.3 Echo color 64 colors
- 2.4 Background color Selectable among 6 colors
- 2.5 Range shift Range: 5-3,000 m, Shift: 0-2,000 m, Expansion range: 5-200 m
- 2.6 Display mode Single-frequency, Dual-frequency, Zoom, NAV 1/2, A-scope
- 2.7 Zoom display Bottom-lock expansion, Bottom zoom, Marker zoom
- 2.8 Picture advance speed 7 steps (Lines/TX: Stop, 1/16, 1/8, 1/4, 1/2, 1/1, 2/1, 4/1), Synchronize w/ ship's speed
- 2.9 Alarm Fish (Normal/Bottom), Water temperature, Bottom
- 2.10 Automatic indication Automatic gain adjust (fishing/cruising), Automatic range Water temperature graph (optional sensor required)

3 INTERFACE

- 3.1 Number of port NMEA0183 Ver.1.5/2.0/3.0 (I/O)..... 1 port
- 3.2 Input data GGA, GLL, GNS, HDG, HDT, MDA, MTW, MWV, RMA, RMC, VHW, VTG
- 3.3 Output data DBS, DBT, DPT, MTW*, TLL, VHW
*: Optional sensor required

4 POWER SUPPLY

- 4.1 Display unit 12-24 VDC: 2.3-1.2 A
- 4.2 Rectifier (PR-62, option) 100/110/220/230 VAC, 1 phase, 50/60Hz

5 ENVIRONMENTAL CONDITIONS

- 5.1 Ambient temperature -15°C to +55°C
- 5.2 Relative humidity 93% at +40°C
- 5.3 Degree of protection Panel: IPX2, Chassis: IPX0

6 COATING COLOR

- 6.1 Display unit N2.5