

Intellian

# C700 INTRODUCTION



# IRIDIUM CERTUS SERVICE CLASSES



- ◆ C700 supports Certus 350 in the upload direction.
- ◆ Certus 700 in download.

*Fastest L-band speeds!*

## Iridium® Services for Maritime

The diagram features a globe with a network of lines representing satellite connections. Five callout boxes point to different service classes, each with a specific speed and list of capabilities.

Service Class	Speed	Category	Capabilities
Iridium Narrowband	2.4 Kbps	NARROWBAND	Telemetry, Asset Tracking, SSAS, LRIT, Vessel Monitoring System (VMS), Global Maritime Distress & Safety System (GMDSS)*
Iridium Certus® 20	22 Kbps	MIDBAND	IoT Connected Ship, Regulatory Compliance: SSAS, Man-Over-Board (MOB), Vessel Monitoring System (VMS), Autonomous Systems, Cargo Tracking, GMDSS*
Iridium Certus® 100	88 Kbps	MIDBAND	Email, Messaging, and Web Browsing, Multiple High-Quality Voice Lines, Electronic Chart Display and Information System (ECDIS) Updates, IoT Connected Ship, Regulatory Compliance: SSAS, LRIT, Citadel, VMS, e-Log, Autonomous Water Craft, GMDSS*
Iridium Certus® 700	704 Kbps	BROADBAND	Email, Messaging, and Web Browsing, Multiple High-Quality Voice Lines, Database Sync, File Transfer, Weather Data, Hybrid Cellular / VSAT System, Remote Diagnostics, Engine Monitoring, Fuel Monitoring, Oceanographic Data, Buoy Data, Messaging Apps, Smartphone Access, Regulatory Compliance: SSAS, LRIT, Citadel, VMS, e-Log, Prepaid Enablement, Cargo Tracking, Autonomous Water Craft, GMDSS*
Iridium Certus® 200	176 Kbps	BROADBAND	Email, Messaging, and Web Browsing, Multiple High-Quality Voice Lines, ECDIS Updates, Remote Diagnostics, Engine, and Fuel Monitoring, Autonomous Water Craft, Regulatory Compliance: SSAS, LRIT, Citadel, VMS, e-Log, Hybrid Cellular / VSAT System, Smartphone Access, GMDSS*
Iridium Certus® 350	352 Kbps	BROADBAND	Email, Messaging, and Web Browsing, Multiple High-Quality Voice Lines, GMDSS*

© 2020 Iridium Satellite LLC. Iridium, the Iridium logo, and Iridium Certus are registered trademarks of Iridium Satellite LLC and its affiliates. All other registered marks, trademarks, service marks and logos are property of their respective holders. Information is subject to change without notice.

## WHAT'S IN THE BOX?

### STAND-ALONE VERSION:

- ◆ Above Deck Unit (ADU)
- ◆ 25 meter Antenna Cable (TNC/TNC)
- ◆ Drilling Template
- ◆ Below Deck Unit (BDU)
- ◆ 1 meter DC Power Cable
- ◆ Quick Installation Guide
- ◆ Weight: 20 kg / 44 lbs (Rack mount version)
- ◆ Size: 52 x 52 x 51 cm / 20.5 x 20.5 x 20 inch



## WHAT'S IN THE BOX?

### RACK MOUNT VERSION:

- ◆ Above Deck Unit (ADU)
- ◆ 25 meter Antenna Cable (TNC/TNC)
- ◆ Drilling Template
- ◆ Below Deck Unit (BDU)
- ◆ 1 meter DC Power Cable
- ◆ Quick Installation Guide
- ◆ AC/DC Power Adapter (incl. EU and US Power Cable)
- ◆ 19" Rack Mount Panel and Cable Support Bracket




## BELOW DECK UNIT (BDU) TYPES

- ◆ Available in two versions
  - Stand-alone (bulkhead) version:
    - Typically as the primary connection
    - Size: 280 x 183.5 x 41 mm / 11" x 7.2" x 1.45 in
    - Weight: 2 kg / 4.4 lb
  - 19" Rack (all-in-one) version:
    - For instance as a VSAT back-up
    - 1U
    - AC/DC Power Adapter included




## OPTIONAL ITEMS

- ◆ AC/DC Power Adapter with US and EU Power Cables
- ◆ 19" Rack Mount bracket with Cable Support
- ◆ Antenna Pole Mount Kit




## BEST-IN-CLASS PERFORMANCE

- ◆ Resilient and reliable technology.
- ◆ Solid-state antenna, no moving parts.
- ◆ 12 patch configuration for optimal satellite tracking and signal reception in any weather or sea condition.
- ◆ Excellent low elevation angle performance handling heavy ship motion.
- ◆ Optimal satellite and beam handover ensuring seamless voice and data connectivity.



## ETHERNET-OVER-COAX

- ◆ Integrated Iridium BCX core module in antenna.
- ◆ Longer cable runs and lower cost at new installations.
- ◆ 50 Ohm coax cable RF specifications:
  - Max. DC resistance: 1.3 Ohm
  - Max. RF loss @ 900 MHz: 13.5 dB (incl. plugs)
- ◆ Reuse existing coax cable onboard for retrofits, saving time and installation cost.
- ◆ No cable calibration required.






INTELLIAN C700

## ALL-IN-ONE SOLUTION

- ◆ Analog Terminal Adapter (ATA)
- ◆ PABX
- ◆ Router
- ◆ Power over Ethernet (PoE)
- ◆ WAN
- ◆ Wi-Fi
- ◆ Firewall
- ◆ No hidden cost in additional equipment, installation and configuration, less points of failure




# BELOW DECK UNIT


## Front Side



## Rear Side



# INTERFACES



## USER FRIENDLY

- ◆ AptusLX – intuitive and easy to use.
- ◆ Embedded in terminal
- ◆ Accessible via LAN and Wi-Fi from a Smartphone, tablet or PC.
- ◆ Login locally onboard and from remote over-the-air.
- ◆ Go to <https://portal.certus.local/>



## THE PERFECT VSAT COMPANION

- ◆ True Global Coverage – Pole to Pole
- ◆ Fastest L-band back-up for VSAT – both in uplink and downlink.
- ◆ Up to 352 kbps in upload and 704 kbps download.
- ◆ Up to 256 kbps QoS Streaming.
- ◆ Supports multiple users.
- ◆ Low-latency (LEO constellation).
- ◆ Future-proof data speeds.

